

ALF 4047

Applications

| Standards | | |
|--------------------|--------------------|--|
| AWS 5.8 | Al-Si 12 | |
| EN ISO 3677 | B-AL88Si - 575/585 | |
| EN ISO 18273 | Al 112 | |
| EN 1044 | AL 104 | |
| Product Features a | nd Advantages | |

Generally used for aluminium and aluminium alloys brazing. Prefably used for mass production for easy use due to containing flux.

It has wide range of use such as pipe connections, air conditioning and cooling, aluminium motor blocks, aluminium radiators and pipes.

Alüminyum Sert Lehim Alaşımları - Sert Lehim Teli

| Working Temperature (°C) | | Melting Temperature (°C) | | Density (gr/cr | m³) Conductivity | Conductivity (Sm/mm ²) | |
|--------------------------|------------------------|--------------------------|-----------------------|---------------------|-----------------------------|------------------------------------|--|
| 590 | | 575-590 | | 2.65 | 2 | 21 | |
| Packaging I | nformation | | | | | | |
| Product Code | Diameter x Length (mm) | Quantity per Box | Box Gross Weight (kg) | Boxes per Outer Box | Outer Box Gross Weight (kg) | Packaging Type | |
| 80414BKA04 | 2.00x500 | 1.00 KG | 1.10 | 1 | 1.10 | Carton Envelope | |